## A report on KAT-7 status

**Tony Foley** tony.foley@ska.ac.za



Department: Science and Technology **REPUBLIC OF SOUTH AFRICA** 















#### **KAT-7 overview**





#### **Reserve 21.44E 30.71S**





### **KAT-7** Now

- 7 composite 12m dishes
- Altaz mount, prime focus
- 5 operational with uncooled receivers
- Cryogenics have been tested
- Lband (1200-1950MHz)
- 256MHz instantaneous IF
- **RF over fibre links**
- LOFAR containers for digital







#### **KAT-7 Correlator**



- FX type
- Uses the SPEAD (Streaming Protocol for Exchange of Astronomical Data) for internal data streaming
- 'KAT-7' 16 inputs May 2011 (7 existing + 1 MeerKAT dual pol)
- Fringe and delay stopping now <u>working</u>! (cm accuracy)
- Continuum mode and line modes (will support at least 8192 channels)
- Tied array option for Pulsars, VLBI etc.
- Will be used for more commissioning & some science





### **The Good**

- Power on site with Diesel backup
- 10Mbps Network allows remote tests
- Webcams allow remote checks
- Convenient weekly flights for maintenance and ops
- Holography shows (final) dishes 1mm RMS good enough for 2cm wavelength (15GHz) - excellent for 20cm
- KAT7 correlator seems to function correctly in continuum mode
- **RFI from Losberg does not leak through the mountain**
- Interferometry to start in earnest ASAP

# **KAT-7 dish moulding**



#### From the mountain













- Weather (rain and lightning)
  - Drips if heavy thunderstorm
  - Drops in ESKOM power- problems for cold receivers
- Wind
- Dust + rain = Mud off the road
- **RFI from cherry-picker**











### What is to be done

- UPS to bridge 40 second gap for diesel to power up
- Possible change of technology for cryogenic cycle for MeerKAT (Stirling to ..)
- Update in brake/motor assemblies
- Retire FF